


Dovetail twistlock

TLA-ANC-DVTL-01

Section 2 — Container Anchoring / Foundations



CATEGORY 2
Container Anchoring /
Foundations

1 PRODUCT OVERVIEW

Originally developed for securing containers to ship decks when used with a matching dovetail slipper. Handle position acts as visual locked/unlocked indicator. Low profile design. Multiple market variants available. Left-hand is standard; right-hand available on request (6–8 week lead time).



2 SPECIFICATIONS AT A GLANCE

SKU / Part No.	TLA-ANC-DVTL-01
Material	Heat Treated Steel
Load Rating	MBL: 500 kN tension / 420 kN shear / 2000 kN compression
Finish	Hot Dip Galvanised
Applicable Standard	ISO 1161
Unit Weight	5.8 kg

3 LOAD & PERFORMANCE DATA

Load Rating (SWL / MBL)	MBL: 500 kN tension / 420 kN shear / 2000 kN compression
-------------------------	--

4 DIMENSIONS & WEIGHT

Dimension	Value
Overall Dimensions (L × W × H)	<i>On application</i>
Unit Weight	5.8 kg

5 MATERIALS, FINISH & COMPLIANCE

Material / Construction	Heat Treated Steel
Finish / Coating	Hot Dip Galvanised
Applicable Standards	ISO 1161
Compatibility / Fitment	<i>On application</i>
Country of Origin	<i>On application</i>

6 APPLICATIONS

- Container-to-deck securing (ships and shore)
- container-to-structure or structure-to-container connections
- combined with dovetail slipper for removable installations

7 SAFETY NOTICES

⚠ SAFETY

Never exceed the stated safe working load. Inspect the unit and mating corner castings for damage before each use.

8 DRAWINGS, 3D MODELS & LATEST REVISIONS

CHECK FOR THE LATEST REVISION



This datasheet

DRAFT A · 2026-08-20 — verify current issue online

2D dimensioned drawing

Included in this document (page 3) — verify latest revision online


3D model (STEP)

Available on request (STEP) — verify latest version online


Scan the QR code or visit [twistlockafrica.co.za/go/tla-anc-dvtl-01](https://www.twistlockafrica.co.za/go/tla-anc-dvtl-01) to confirm you hold the latest issue of this datasheet, drawing and 3D model before manufacturing or installation.

ORDERS & ENQUIRIES · info@twistlockafrica.co.za · Tel +27 11 609 7873 · WhatsApp +27 82 825 1852 · www.twistlockafrica.co.za · Pricing on application (ZAR, ex VAT)


9 DIMENSIONED DRAWING / PRODUCT SHEET — TLA-DRW-ANC-DVTL-01 DRAFT A (FROM 3D MODEL)



FRONT
-- 192 · 1208 mm




RIGHT
-- 124 · 1192 mm



TOP
-- 208 · 1124 mm

Overall envelope from 3D model: 208 × 124 × 192 mm · third-angle · do not scale · detail dimensions per 3D model (STEP on request)

LOADS		SHEAR [kN]	TENSION [kN]
BREAKING LOAD	BL	420	500
SAFE WORKING LOAD	SWL	On application	On application
TOTAL WEIGHT: 5.8 kg			



DOVETAIL TWISTLOCK 45°

Twistlock Africa (Pty) Ltd
Gauteng, South Africa
www.twistlockafrica.co.za



TLA-ANC-DVTL-01

DRAFT A · 2026-08-22

ralph@twistlockafrica.co.za
+27 (0)82 825 1852
Pricing & certification on application



LATEST REV