


Horizontal twistlock with end plate

TLA-ATT-HTLEP-01

Section 8 — Container Attaching



1 PRODUCT OVERVIEW

Manufactured using forged steel; self-coloured finish. SWL 12T tension. Capacity ratings: 24T tension, 34T shear, 20.8T compression. Tare weight 9.1 kg. 4 tapped holes on adapter plate. Compatible with all ISO type shipping containers.



2 SPECIFICATIONS AT A GLANCE

SKU / Part No.	TLA-ATT-HTLEP-01
Material	Forged steel
Load Rating	SWL: 12T tension
Finish	On application
Applicable Standard	ISO 1161
Unit Weight	9.1 kg

3 LOAD & PERFORMANCE DATA

Load Rating (SWL / MBL)	SWL: 12T tension; capacity: 24T tension / 34T shear / 20.8T compression
-------------------------	---

4 DIMENSIONS & WEIGHT

Dimension	Value
Overall Dimensions (L × W × H)	On application
Unit Weight	9.1 kg

5 MATERIALS, FINISH & COMPLIANCE

Material / Construction	Forged steel
Finish / Coating	On application
Applicable Standards	ISO 1161
Compatibility / Fitment	On application
Country of Origin	On application

6 APPLICATIONS

- Attaching walkways, platforms, solar structures and equipment to container side corner casting apertures

7 SAFETY NOTICES

⚠ SAFETY

Never exceed the stated safe working load. Inspect the unit and mating corner castings for damage before each use.

8 DRAWINGS, 3D MODELS & LATEST REVISIONS

CHECK FOR THE LATEST REVISION



This datasheet

DRAFT A · 2026-08-20 — verify current issue online

2D dimensioned drawing

On request — verify availability online

3D model (STEP)

In production — check availability online

Scan the QR code or visit [twistlockafrica.co.za/go/tla-att-htlep-01](https://www.twistlockafrica.co.za/go/tla-att-htlep-01) to confirm you hold the latest issue of this datasheet, drawing and 3D model before manufacturing or installation.

ORDERS & ENQUIRIES · info@twistlockafrica.co.za · Tel +27 11 609 7873 · WhatsApp +27 82 825 1852 · www.twistlockafrica.co.za · Pricing on application (ZAR, ex VAT)