

Tow hitch — Off road

TLA-MOV-HITCHR-01

Section 3 — **Container Moving**



1 PRODUCT OVERVIEW

Completely different design from TLA's castor-wheel tow hitch — built specifically for off-road and agricultural towing conditions. Attaches to the front bottom corner castings of any standard ISO 20ft or 40ft container. The vehicle-side connection uses a standard 2 5/16" ball hitch, compatible with the standard towbar of any South African 4×4 bakkie, tractor or telehandler. Used as a system with TLA's off-road container wheel kit: the tow hitch connects the front of the container to the towing vehicle, while one pair of off-road wheels supports the rear. The vehicle steers; the container trails. KEY FEATURES: • ISO 1161 corner casting connection on container side — fits any standard ISO container • Standard 2 5/16" ball hitch on vehicle side — fits any SA 4×4 towbar • 6.4T gross towing capacity • Heavy gauge steel construction for rough ground conditions • Suitable for 20ft and 40ft ISO containers • System partner: TLA off-road container wheel kit (rear end)

LAUNCHING AT ELECTRAMINING 2026.

[PHOTO REQUIRED — Tow hitch — Off road: hero shot, 3/4 angle on neutral background]

2 SPECIFICATIONS AT A GLANCE

SKU / Part No.	TLA-MOV-HITCHR-01
Material	Heavy gauge steel
Load Rating	6.4T gross towing capacity
Finish	On application
Applicable Standard	ISO 1161 (container side); 2 5/16" ball hitch (vehicle side)
Unit Weight	On application

3 LOAD & PERFORMANCE DATA

Load Rating (SWL / MBL)	6.4T gross towing capacity
-------------------------	----------------------------

4 DIMENSIONS & WEIGHT

Dimension	Value
Overall Dimensions (L × W × H)	<i>On application</i>
Unit Weight	<i>On application</i>

5 MATERIALS, FINISH & COMPLIANCE

Material / Construction	Heavy gauge steel
Finish / Coating	<i>On application</i>
Applicable Standards	ISO 1161 (container side); 2 5/16" ball hitch (vehicle side)
Compatibility / Fitment	<i>On application</i>
Country of Origin	<i>On application</i>

6 APPLICATIONS

- Off-road container towing on farms, mine sites and construction sites
- used in combination with TLA off-road container wheel kit
- towing with 4×4 bakkies, tractors and telehandlers

7 SAFETY NOTICES

⚠ SAFETY

Never exceed the stated safe working load. Inspect the unit and mating corner castings for damage before each use.

8 DRAWINGS, 3D MODELS & LATEST REVISIONS

CHECK FOR THE LATEST REVISION



This datasheet

DRAFT A · 2026-08-20 — verify current issue online

2D dimensioned drawing

On request — verify availability online

3D model (STEP)

In production — check availability online

Scan the QR code or visit [twistlockafrica.co.za/go/tla-mov-hitchr-01](https://www.twistlockafrica.co.za/go/tla-mov-hitchr-01) to confirm you hold the latest issue of this datasheet, drawing and 3D model before manufacturing or installation.

ORDERS & ENQUIRIES · info@twistlockafrica.co.za · Tel +27 11 609 7873 · WhatsApp +27 82 825 1852 · www.twistlockafrica.co.za · Pricing on application (ZAR, ex VAT)